



UNI EN ISO 9001:2015
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

KR 33

Rev. 1 - January 2020

REVIVER OF THE NATURAL COLOUR WATER REPELLENT SEALER

KR 33 is an extremely versatile protective formula, solvent based, allowing a high penetration capacity into the material in depth. KR 33 has a pleasant reviving effect of the natural colours/shades ("wet effect") of the treated materials and performs excellent waterproofing capacity due to the organ-silicon compounds.

It is a sealer of long-lasting effects that does not make film on surface and keep unchanged the natural transpiration capacity of the treated material.

FUNCTION

SEALER, WATER REPELLENT, REVIVER OF THE NATURAL COLOUR FOR POLISHED MARBLE AND GRANITE (not rough or flamed or unfinished)

LINE

PROTECTION

PROFESSIONAL

INDICATION

Makes water- and dirt-repellent the treated surfaces. Revives the natural colour, leaving the surface uniformly glossy, without changing the colour and the physical properties of the material.

It doesn't anyway protect against acid substances.

KR 33 is indicated for indoor application. Not suitable for outdoor use

MATERIALS

All absorbing natural stone, polished granites and marbles

Do not use on white or light crystalline marble (for these marbles, Ever Clean and Imperston are suggested)

USAGE

Apply undiluted to dry and clean surfaces with a cotton cloth and let the material impregnate according to the porosity. For very porous materials, after drying, may be necessary to repeat the application.

Important: Avoid the product dry on the surface. Remove any excess of unabsorbed product with a clean (and possibly white) cotton cloth before it dries.

TEST

Testing a small, hidden area is recommended before application to determine consumption, drying time and to verify appearance and protection degree.

COMPOSITION

Contains silicon compounds and solvents

TECHNICAL INFORMATION

Evaporation time of solvent 20-40 minutes (depending on ambient conditions).

Consumption: 50 to 200 g/m² depending on porosity of the material treated

NOTE

Solvent-based product: inflammable. Apply in well ventilated areas while wearing impermeable gloves.

For more information about safety, see product label or the Material Safety Data Sheet.

Keep out from the reach of children



IMPORTANT

Apply to completely dry, clean and free from greasy substances surfaces.

Apply on polished materials (not rough or flamed).

Not suggested for use on white or on very light colour or on crystalline marbles; in this case use **Imperston** or **Ever Clean**.

Protection capacity is fully operative after 18 to 24 from the application, depending on environmental conditions (temperature, humidity, ventilation, etc.)

PACKAGING

250 ml., 1 L., 5 L., 10 L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION